



RA12-90A(12V90Ah)

Specification

Cells Per Unit	6
Voltage Per Unit	12
Nominal Capacity	90Ah@10hour-rate to 1.80V per cell @25°C
Weight	Approx. 28.0 Kg (Tolerance ±2.0%)
Internal Resistance	Approx. 5.2 mΩ
Terminal	F12(M8)/F15(M6)
Max. Discharge Current	900A (5 sec)
Short Circuit Current	1850A
Design Life	12 years (Float charging)
Recommended Maximum Charging Current	27 A
Reference Capacity	C3 69.8AH C5 80.4AH C10 90.0AH C20 95.2AH
Standby Use Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



RA series is a general purpose battery with 12 years design life in float service. It meets with IEC, JIS, BS and YDT standards. With advanced AGM valve regulated technology and high purity raw material, the RA series battery maintains high consistency for better performance and reliable standby service life. It is suitable for UPS/EPS, Telecom, power grid, medical equipment, emergency light and security system applications.



Dimensions

Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A (25°C)

F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	216.7	163.2	94.4	56.0	33.5	24.6	20.0	16.9	11.3	9.59	4.92
1.65V	210.2	158.9	92.4	54.9	33.0	24.3	19.8	16.7	11.2	9.50	4.88
1.70V	201.7	153.3	89.6	53.6	32.4	23.9	19.4	16.4	11.0	9.38	4.83
1.75V	190.8	145.9	86.0	51.8	31.5	23.3	19.0	16.1	10.8	9.22	4.76
1.80V	176.8	136.5	81.4	49.4	30.4	22.5	18.4	15.6	10.5	9.00	4.67
1.85V	159.3	124.7	75.4	46.4	28.9	21.5	17.6	15.0	10.2	8.72	4.54

Constant Power Discharge Characteristics : WPC (25°C)


F.V/Time	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	373.8	289.5	174.1	106.2	64.5	47.7	39.0	33.0	22.4	19.1	9.83
1.65V	372.3	287.9	172.8	105.4	64.0	47.4	38.7	32.8	22.2	19.0	9.77
1.70V	361.3	280.1	168.6	103.1	63.0	46.7	38.1	32.4	21.9	18.8	9.68
1.75V	347.8	270.6	163.5	100.1	61.6	45.7	37.4	31.8	21.6	18.5	9.55
1.80V	327.9	256.7	156.2	96.0	59.6	44.4	36.4	31.0	21.1	18.1	9.37
1.85V	300.7	237.7	146.3	90.7	57.1	42.6	35.0	29.9	20.4	17.5	9.14

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.


RA12-90A(12V90Ah)




Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use




Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity




Storage Characteristics



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.