



RA12-180FDG (12V180Ah)

RA12-180FDG is GEL Deep cycle battery superiorly designed for frequent cyclic discharge applications under extreme temperature. By using strong grid to insure reliable performance under frequent cyclic discharge use. 400 cycles could be available at 100% DOD. Offering extra-durable cyclic performance, high efficiency of recovery, that is more suitable for solar, mobility, E-toll, marine, deep discharge UPS etc..



Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	180Ah@20hr-rate to 1.75V per cell @25°C
Weight	Approx. 53.5 Kg
Max. Discharge Current	1800 A (5 sec)
Internal Resistance	Approx. 5mΩ
Operating Temperature Range	Discharge: -40°C~60°C Charge:-20°C~50°C Storage: -40°C~60°C
Normal Operating Temperature Range	25°C±5°C
Float charging Voltage	13.6 to 13.8 VDC/unit Average at 25°C
Recommended Maximum Charging Current Limit	36A
Equalization and Cycle Service	14.2 to 14.4VDC/unit Average at 25°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for more than 6 months at 25°C. Self-discharge ratio less than 3% per month at 25°C. Please charge batteries before using.
Terminal	Terminal F9
Container Material	A.B.S. (UL94-HB), Flammability resistance of UL94-V1 can be available upon request.



MH28539




G4M20206-0910-E-16





ISO9001:2000 Certificate

Dimensions

Unit: mm Dimension: 560(L)×125(W)×316(H)



Terminal F9



Constant Current Discharge Characteristics: A (25°C)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.60V	451.3	322.9	259.2	173.7	105.9	63.38	43.80	35.90	29.39	20.24	17.11	9.413
10.0V	438.2	307.3	253.9	171.0	105.4	62.90	43.64	35.73	29.21	20.08	16.95	9.242
10.2V	425.2	296.4	249.9	171.1	104.4	62.42	43.30	35.57	29.04	19.91	16.79	9.071
10.5V	386.3	276.8	240.8	168.5	103.5	61.95	43.13	35.24	28.69	19.75	16.62	8.900
10.8V	352.8	255.4	224.5	162.7	101.0	60.83	41.96	34.40	28.18	19.42	16.46	8.729
11.1V	304.7	230.9	203.7	153.8	95.97	58.13	40.11	32.74	26.97	18.60	15.96	8.215

Constant Power Discharge Characteristics: W (25°C)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
9.6V	4668	3439	2852	1981	1224	747.0	521.3	427.9	350.6	241.7	204.5	112.9
10.0V	4576	3334	2806	1958	1221	743.0	521.5	427.4	349.7	240.5	203.2	110.9
10.2V	4523	3246	2774	1963	1212	738.6	519.2	426.5	348.5	238.9	201.4	108.9
10.5V	4167	3059	2677	1936	1201	733.2	517.2	422.5	344.3	237.0	199.5	106.8
10.8V	3839	2853	2503	1874	1178	723.8	503.1	412.9	338.1	233.0	197.5	104.7
11.1V	3411	2609	2279	1777	1128	697.0	481.3	392.9	323.6	223.2	191.6	98.58


All mentioned values are average values.

RA12-180FDG

12V180Ah




Life characteristics of cyclic use




Storage characteristic



Charge characteristic curve for cyclic use



Discharge characteristic curve



Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
GEL Battery	6V&12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%
	2V	60%	75%	85%	88%	92%	99%	100%	103%	105%	106%
AGM Battery	6V&12V	46%	66%	76%	83%	90%	98%	100%	103%	107%	109%
	2V	55%	70%	80%	85%	92%	99%	100%	104%	108%	110%

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/cell	1.75V	1.70V	1.60V
Discharge Current (A)	(A) ≤ 0.2C	0.2C < (A) < 1.0C	(A) ≥ 1.0C

Maintenance & Cautions

Cycle service
※ Avoid battery over discharge, especially battery series connection use.
※ Charged with recommend voltage, ensure battery can be full recharged.
In general, recharge capacity should be 1.1-1.15 times discharge capacity.
※ Effect of temperature on cycle charge voltage: -4mV/°C/Cell.
※ There are a number of factors that will affect the length of cyclic service.
The most significant are depth of discharge, ambient temperature, discharge rate, and the manner in which the battery is recharged.
Generally speaking, the most important factors is depth of discharge.

Charge the batteries at least once every six months, if they are stored at 25°C.

Charging Method:

Constant Voltage	-0.2Cx2h+2.4~2.45V/Cellx24h, Max. Current 0.3CA
Constant Current	-0.2Cx2h+0.1CAx12h
Fast	-0.2Cx2h+0.3CAx4.0h