

# DG6-280(6V280Ah)



## Specification

Cells Per Unit	3
Voltage Per Unit	6
Capacity	280Ah@20hr-rate to 1.75V per cell @25°C
Weight	Approx. 41.7 Kg (Tolerance ±3.0%)
Internal Resistance	Approx. 3.0 mΩ
Terminal	F14(M8)
Max. Discharge Current	2800A (5 sec)
Design Life	15 years (floating charge)
Max. Charging Current	56.0 A
Reference Capacity	C3 191.1AH C5 215.5AH C10 246.0AH C20 280.0AH
Float Charging Voltage	6.80 V~6.90 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	7.10 V~7.20 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -40°C~60°C Charge: -20°C~50°C Storage: -40°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C, and then recharging is recommended. Monthly Self-discharge ratio is less than 2% at 20°C. Please charged batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



DG (Deep Cycle GEL) series is pure GEL battery with 15 years floating design life, it is ideal for standby or frequent cyclic discharge applications under extreme environments. By using strong grids, high purity lead and patented GEL electrolyte, the DG series offers excellent recovery capability after deep discharge under frequent cyclic discharge use, and it can offers 2 times cyclic life than the standard series. It is suitable for solar & wind system, marine, deep discharge UPS etc.



ISO 9001



ISO 14001







OHSAS 18001



MH 28539



## Dimensions



F14 TERMINAL

Length	295±2mm (11.6 inches)
Width	178±2mm (7.01 inches)
Height	346±2mm (13.6 inches)
Total Height	351±2mm (13.8 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit:mm

### Constant Current Discharge Characteristics : A(25°C)

F.V/Time	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	371.8	243.9	152.1	92.9	69.6	55.6	46.6	31.5	26.0	14.6
1.65V	355.4	234.2	146.8	89.9	67.5	54.1	45.4	31.2	25.7	14.3
1.70V	332.9	223.8	142.1	87.0	65.7	52.6	44.2	30.7	25.3	14.2
1.75V	309.8	213.9	136.9	83.9	63.7	51.3	43.1	30.3	25.0	14.0
1.80V	286.0	204.5	131.6	80.9	61.7	49.8	42.0	29.7	24.6	13.9
1.85V	237.4	176.1	118.1	74.2	57.1	46.3	39.2	27.9	23.2	13.2

### Constant Power Discharge Characteristics : WPC(25°C)

F.V/Time	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	738.5	503.5	324.7	200.1	151.2	121.2	102.1	69.9	58.1	32.6
1.65V	709.9	487.5	315.9	194.7	147.5	118.4	99.9	69.2	57.4	32.2
1.70V	681.2	471.5	307.0	189.3	143.8	115.6	97.6	68.4	56.6	31.8
1.75V	643.1	455.3	297.6	183.5	140.1	113.1	95.5	67.6	56.0	31.4
1.80V	602.2	439.6	287.9	177.8	136.3	110.2	93.3	66.6	55.3	31.2
1.85V	506.8	382.4	259.8	163.8	126.5	102.8	87.3	62.6	52.2	29.6


(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.

The battery must be fully charged before the capacity test. The C<sub>20</sub> should reach 95% after the first cycle and 100% after the third cycle.


# DG6-280(6V280Ah)




## Discharge Characteristics Curve




## Charge Characteristic Curve for Cycle Use(IU)




## Cycle Life in Relation to Depth of Discharge




## Relationship Between Charging Voltage and Temperature




## Temperature Effects on Capacity




## Storage Characteristics



## Effect of Temperature on Long Term Life



## Relationship of OCV And State of Charge(20°C)



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.