



RL2-500A(2V500Ah)

Specification

Cells Per Unit	1
Voltage Per Unit	2
Nominal Capacity	500Ah@10hour-rate to 1.80V per cell @25°C
Weight	Approx. 25.5 Kg (Tolerance ± 3.0%)
Internal Resistance	Approx. 0.60 mΩ
Terminal	F10(M8)
Max. Discharge Current	2000A (5 sec)
Short Circuit Current	4210A
Design Life	20 years (Float charging)
Max. Charging Current	100 A
Reference Capacity	C1 275.0AH C3 387.0AH C5 436.0AH C10 500.0AH
Standby Use Voltage	2.27 V~2.30 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	2.43 V~2.47 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: -0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ± 5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging be stored for up to 6 months at 25°C and then recharging than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



RL series is a general purpose battery with 20 years design life in float service. It meets with heavy duty grids, thicker plates, special additives and advanced AGM valve regulated technology, the RL series battery provides consistent performance and long service life. The new grid design effectively reduces the internal resistance, which provides higher specific energy density and excellent high rate discharge characteristics. It is suitable for communications back-up power and EPS/UPS applications.



ISO 9001



ISO 14001



OHSAS 18001






MH 28539



G4M20206-0910-E-16

Dimensions



F10 TERMINAL

Length	196±2mm (7.72 inches)
Width	171±2mm (6.73 inches)
Height	330±2mm (13.0 inches)
Total Height	342±2mm (13.5 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A (25°C)

F.V/Time	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR
1.60V	478.7	305.5	188.1	141.0	113.5	94.3	63.4	52.7
1.65V	459.6	295.0	182.1	136.7	110.4	91.9	62.7	52.1
1.70V	439.3	285.4	176.1	133.0	107.4	89.5	61.7	51.3
1.75V	419.9	275.0	170.0	129.0	104.7	87.2	60.9	50.6
1.80V	401.3	264.5	163.9	125.0	101.7	85.0	59.8	50.0
1.85V	345.6	237.2	150.2	115.6	94.5	79.3	56.2	47.1

Constant Power Discharge Characteristics : WPC (25°C)


F.V/Time	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR
1.60V	869.5	574.1	356.6	269.4	217.9	181.8	123.8	103.7
1.65V	843.6	557.6	346.9	262.1	212.8	177.8	122.7	102.6
1.70V	814.4	542.8	337.3	256.1	207.8	173.8	121.1	101.2
1.75V	786.4	526.1	327.0	249.6	203.3	170.0	119.6	99.9
1.80V	759.2	509.0	316.9	242.8	198.1	166.2	117.8	98.8
1.85V	660.4	459.3	291.9	225.5	184.9	155.5	110.9	93.1

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values. The battery must be fully charged before the capacity test. The C10 should reach 95% after the first cycle and 100% after the third cycle.


RL2-500A(2V500Ah)




Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use




Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity




Storage Characteristics



Effect Of Temperature On Long Term Life



Charge Characteristic Curve For Standby Use



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.

HENGYANG RITAR POWER CO.,LTD.
 URL: www.ritarpower.com

Add: No.1 Huagong Road, Songmu Industrial Park, Shigu District, Hengyang, Hunan, China 421001
 Tel: +86-734-8595528 Fax: +86-734-8595518 E-mail: sales@ritarpower.com

Version 20A-0